

# **J** Series


## Explosion Proof Edge Lit LED Exit Light



#### Certifications:

- Marking UL844 (North American)
  - Olass I, Division 1, Groups B, C, D
  - Olass I, Division 2, Groups A, B, C, D
  - Olass II, Division 1, Groups E, F, G
  - Olass II, Division 2, Groups F, G
  - Class III

UL Marking
UL924
UL844
UL 121201/CSA NO.213
CSA C22.2 No.137-18
Temperature Class (T-Rating)-T6






## J Series Explosion Proof Edge Lit LED Exit Light

#### Key Features:

- 1) Low energy consumption (3W/5W).
- 2) 3-hour emergency operation.
- 3) Alternate exit legend and languages available.
- 4) Provided with 3/4 " NPT or M25 conduit hubs.
- 5 Long lifespan up to 50,000 hours.
- 6) Multiple installation options: wall mounting, pendant mounting, and pendant mounting with safe-wire.
- 7) Working temperature ranges from -40°F to 140°F.
- 8 5-year warranty.
- 9 Edge-lit sign



## Technical Data:


Model	Wattage	Operating Voltage	CRI	Color Temperature	Emergency Time
EX-3W JNGD180	3W(Max)	AC100-277V AC100-347V	>70	Red or Green	3 hours
EX-5W JNGD180	5W(Max)				

## Packing Information:

Model	Quantity/Carton		Net Weight	Gross Weight
J	2 Pcs	18.50x18.50x10.24inch	13.23 lbs	30.86 lbs



## J Series Explosion Proof Edge Lit LED Exit Light



#### Mounting Methods and Accessories:

