

# **V** Series

# Explosion Proof Edge Lit LED Exit Light















#### Certifications:

- Marking ATEX
  - II2 G Ex ib IIC T4 Gb
  - II2 D Ex tb IIIC T80°C Db IP66
- Marking IECEx
  - Ex ib IIC T4 Gb
  - Ex tb IIIC T80°C Db IP66
- Marking Marine
  - **O** UL 924

- Marking UL844 (North American)
  - Olass I, Division 2, Groups A, B, C, D
  - Olass II, Division 1, Groups E, F, G
  - Class II, Division 2, Groups F, G
  - Class III
- Ambient Temperature:
  - -4°F to 140°F(-20°C to 60°C)
- IP66

#### Standard Materials:

Housing: Aluminum

EXIT sign: Tempered glass

Hardware: Stainless steel

Mounting Sling: Stainless steel



## V Series Explosion Proof Edge Lit LED Exit Light


### Key Features:

- 1 Lightweight and compact structure.
- (2) Integrated junction box for driver with emergency backup.
- (3) Ingress protection rating IP66.
- (4) Low energy consumption (1W/2W/5W)
- (5) 3-hour emergency operation.
- 6 Stainless-steel exposed fasteners with high corrosion resistance.
- (7) High vibration and impact resistance.

#### Additional Features:

- Alternate exit legend and languages available.
- 5-year warranty.
- Long lifespan up to 50,000 hours.
- Working temperature ranges from -4°F(-20°C) to 140°F(60°C).

## Catalog Number Logic:



- (1) PRODUCT CATEGORY
  - Explosion-proof light
- 2 WATTAGE
  - 1W/2W/5W
- 3 PRODUCT SERIES
- 4 DIMMING OPTION

  N= Non-dimmable

- 5 CCT
  - Z=R: Red
  - Z=G: Green
- 6 BEAM ANGLE
  - 180°

#### **Technical Data:**


Model	Wattage	Operating Voltage	ССТ	Emergency Time
EX-1W VNRD180; EX-1W VNGD180	1W	AC100-277V/DC12-48V 50/60 Hz	2200K-7000K	3 hours
EX-2W VNRD180; EX-2W VNGD180	2W			
EX-5W VNRD180; EX-5W VNGD180	5W			



# V Series Explosion Proof Edge Lit LED Exit Light


## Dimension:

16.12inch 409mm 13.74inch 349mm 11.08inch/12mm




## Mounting:


#### Pendant Mounting:







Pipe Mounting:



## Packing Information:

Model	Quantity/Carton	Packing Size	Net Weight	Gross Weight
V Series	2 Pcs	18.50x18.50x10.24inch/470x470x260mm	3.3 kg/ 7.28 lbs	7 kg/ 15.43 lbs